

HeatSeeker Technical Information

Code		HSE056	HSE095	HSE125	HSE170	HSE210	
Rated Heating Capacity	Watts	5600	9500	12500	17000	21000	
	BTU	19000	32500	42600	58000	71600	
Input Power Heating	Watts	1160	1939	2660	3500	4400	
Running Current Heating	Amps	3.6	8.8	12.7	16.7	21	
Start-Up Current	Amps	15	35	46	65	84	
Required Power Supply *	Amps	6	10	16	20	32	
COP		5.0	5.0	4.7	4.7	4.7	
Number of Compressors		1			1		
Compressor Type		Rotary			Scroll		
Number of Fans		1			1		
Input Power of Fan	Watts	25	30	128	150	360	
Fan Rotation Speed	rpm	950	950	900	850	850	
Noise Level	dB(A)	55	58	55	58	58	
Water Connection	inches	1½	1½	1½	1½	1½	
Water Flow Rate	m³/h	3 - 5	4 - 7	6 - 8	7 - 11	9 - 14	
Water Pressure Drop	KPa	12	15	25	25	30	
Unit Dimension	L	995	1085	1085	660	660	
	W	360	370	370	660	660	
	H mm	550	615	615	860	960	
Packing Dimension	L	1090	1170	1170	700	700	
	W	390	415	415	740	740	
	H mm	580	645	645	1010	1110	
Refrigerant	R407C	g		1500	1900	2100	
Weight	Net/Gross	kg	50 / 53	63 / 67	63 / 75	99 / 114	100 / 116

*Please note all heaters are 230 volt single phase 50Hz.

All heaters must be protected by a motor rated fuse.

- Type B trips between 3 and 5 time full load current;
- Type C trips between 5 and 10 times full load current; and
- Type D trips between 10 and 20 times full load current.